

[illegible]

[illegible]

Steel Design (Track 2) Beam 208 Check 1

*****					Y	PROPERTIES	
MEMBER 208						IN	INCH UNIT
DESIGN CODE					---	Z	
AISC-1989							
<---LENGTH (FT)= 1.00 --->							

0.0 (KIP-FEET)							
PARAMETER					L8	STRESSES	
IN KIP INCH					L8 L8	IN	INCH
KL/R-Y= 12.43					L8	FA	= 21.03
KL/R-Z= 12.43					L8	fa	= 0.58
UNL = 12.00					L8	FCZ	= 23.76
CB = 1.00						FTZ	= 23.76
CMY = 0.85					L8 L8	FCY	= 23.76
CMZ = 0.85					L24	FTY	= 23.76
FYLD = 36.00					L14	fbz	= 0.10
NSF = 1.00						fbz	= 0.07
DFF = 0.00						Fey	= 967.24
dff= 0.00						Fez	= 967.24
ABSOLUTE MZ ENVELOPE						FV	= 14.40
(WITH LOAD NO.)						fv	= 0.01
MAX FORCE/ MOMENT SUMMARY (KIP-FEET)							
AXIAL							
SHEAR-Y							
SHEAR-Z							
MOMENT-Y							
MOMENT-Z							
VALUE					0.6	0.0	0.0
LOCATION					0.0	1.0	0.0
LOADING					8	8	8

DESIGN SUMMARY (KIP-FEET)							
RESULT/							
CRITICAL COND/							
RATIO/							
LOADING/							
FX							
MY							
MZ							
LOCATION							
PASS					AISC- H1-3	3.423E-02	8
0.62 C					-0.00	-0.01	0.00

Utilization Ratio

Beam	Analysis Property	Design Property	Actual Allowable		Ratio (Act./Allow.)	Clause	L/C	Ax (in ²)	Iz (in ⁴)	Iy (in ⁴)	Ix (in ⁴)
1	HSST3.5X3.	HSST3.5X3.	0.269	1.050	0.256	AISC- H2-1	28	2.240	4.050	4.050	6.560
2	HSST3.5X3.	HSST3.5X3.	0.275	1.050	0.262	AISC- H2-1	28	2.240	4.050	4.050	6.560
3	HSST3.5X3.	HSST3.5X3.	0.824	1.050	0.785	AISC- H1-3	29	2.240	4.050	4.050	6.560
4	HSST3.5X3.	HSST3.5X3.	0.655	1.050	0.624	AISC- H1-3	11	2.240	4.050	4.050	6.560
5	HSST3.5X3.	HSST3.5X3.	0.533	1.050	0.508	AISC- H2-1	29	2.240	4.050	4.050	6.560
6	HSST3.5X3.	HSST3.5X3.	0.599	1.050	0.570	AISC- H1-3	11	2.240	4.050	4.050	6.560
7	HSST3.5X3.	HSST3.5X3.	0.640	1.050	0.609	AISC- H1-3	8	2.240	4.050	4.050	6.560
8	HSST3.5X3.	HSST3.5X3.	0.222	1.050	0.211	AISC- H1-3	8	2.240	4.050	4.050	6.560
9	HSST3.5X3.	HSST3.5X3.	0.640	1.050	0.609	AISC- H1-3	8	2.240	4.050	4.050	6.560
10	HSST3.5X3.	HSST3.5X3.	0.222	1.050	0.211	AISC- H1-3	8	2.240	4.050	4.050	6.560
11	HSST2.5X2.	HSST2.5X2.	0.729	1.050	0.694	AISC- H1-3	11	1.070	0.998	0.998	1.610
12	HSST3.5X3.	HSST3.5X3.	0.639	1.050	0.609	AISC- H2-1	29	2.240	4.050	4.050	6.560
36	HSST2.5X2.	HSST2.5X2.	0.029	1.050	0.027	AISC- H2-1	8	1.070	0.998	0.998	1.610
56	HSST3.5X3.	HSST3.5X3.	0.325	1.050	0.310	AISC- H1-3	10	2.240	4.050	4.050	6.560
102	HSST2.5X2.	HSST2.5X2.	0.047	1.050	0.045	AISC- H1-3	17	1.070	0.998	0.998	1.610
170	HSST3.5X3.	HSST3.5X3.	0.850	1.050	0.809	AISC- H2-1	8	2.240	4.050	4.050	6.560
190	HSST3.5X3.	HSST3.5X3.	0.850	1.050	0.809	AISC- H2-1	8	2.240	4.050	4.050	6.560
208	HSST2.5X2.	HSST2.5X2.	0.034	1.050	0.033	AISC- H1-3	8	1.070	0.998	0.998	1.610

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Appendix A - STAAD Input and Design Output

Staad Input Data.txt

```

1. STAAD SPACE
INPUT FILE:\Container House\Staad\Container House.STD
2. START JOB INFORMATION
3. ENGINEER DATE 10-FEB-18
4. END JOB INFORMATION
5. INPUT WIDTH 79
6. UNIT FEET KIP
7. JOINT COORDINATES
8. 1 0 0 0; 2 0 0 8; 3 20 0 0; 4 20 0 8; 5 0 8 0; 6 0 8 8; 7 20 8 0; 8 20 8 8
9. 9 1 0 8; 10 1 1 8; 11 0 1 8; 12 2 0 8; 13 2 1 8; 14 3 0 8; 15 3 1 8; 16 4 0 8
10. 17 4 1 8; 18 5 0 8; 19 5 1 8; 20 6 0 8; 21 6 1 8; 22 7 0 8; 23 7 1 8; 24 8 0 8
11. 25 8 1 8; 26 9 0 8; 27 9 1 8; 28 10 0 8; 29 10 1 8; 30 11 0 8; 31 11 1 8
12. 32 12 0 8; 33 12 1 8; 34 13 0 8; 35 13 1 8; 36 14 0 8; 37 14 1 8; 38 15 0 8
13. 39 15 1 8; 40 16 0 8; 41 16 1 8; 42 17 0 8; 43 17 1 8; 44 18 0 8; 45 18 1 8
14. 46 19 0 8; 47 19 1 8; 48 20 1 8; 49 1 2 8; 50 0 2 8; 51 2 2 8; 52 3 2 8
15. 53 4 2 8; 54 5 2 8; 55 6 2 8; 56 7 2 8; 57 8 2 8; 58 9 2 8; 59 10 2 8
16. 60 11 2 8; 61 12 2 8; 62 13 2 8; 63 14 2 8; 64 15 2 8; 65 16 2 8; 66 17 2 8
17. 67 18 2 8; 68 19 2 8; 69 20 2 8; 70 1 3 8; 71 0 3 8; 72 2 3 8; 73 3 3 8
18. 74 4 3 8; 75 5 3 8; 76 6 3 8; 77 7 3 8; 78 8 3 8; 79 9 3 8; 80 10 3 8
19. 81 11 3 8; 82 12 3 8; 83 13 3 8; 84 14 3 8; 85 15 3 8; 86 16 3 8; 87 17 3 8
20. 88 18 3 8; 89 19 3 8; 90 20 3 8; 91 1 4 8; 92 0 4 8; 93 2 4 8; 94 3 4 8
21. 95 4 4 8; 96 5 4 8; 97 6 4 8; 98 7 4 8; 99 8 4 8; 100 9 4 8; 101 10 4 8
22. 102 11 4 8; 103 12 4 8; 104 13 4 8; 105 14 4 8; 106 15 4 8; 107 16 4 8
23. 108 17 4 8; 109 18 4 8; 110 19 4 8; 111 20 4 8; 112 1 5 8; 113 0 5 8
24. 114 2 5 8; 115 3 5 8; 116 4 5 8; 117 5 5 8; 118 6 5 8; 119 7 5 8; 120 8 5 8
25. 121 9 5 8; 122 10 5 8; 123 11 5 8; 124 12 5 8; 125 13 5 8; 126 14 5 8
26. 127 15 5 8; 128 16 5 8; 129 17 5 8; 130 18 5 8; 131 19 5 8; 132 20 5 8
27. 133 1 6 8; 134 0 6 8; 135 2 6 8; 136 3 6 8; 137 4 6 8; 138 5 6 8; 139 6 6 8
28. 140 7 6 8; 141 8 6 8; 142 9 6 8; 143 10 6 8; 144 11 6 8; 145 12 6 8
29. 146 13 6 8; 147 14 6 8; 148 15 6 8; 149 16 6 8; 150 17 6 8; 151 18 6 8
30. 152 19 6 8; 153 20 6 8; 154 1 7 8; 155 0 7 8; 156 2 7 8; 157 3 7 8; 158 4 7 8
31. 159 5 7 8; 160 6 7 8; 161 7 7 8; 162 8 7 8; 163 9 7 8; 164 10 7 8; 165 11 7 8
32. 166 12 7 8; 167 13 7 8; 168 14 7 8; 169 15 7 8; 170 16 7 8; 171 17 7 8
33. 172 18 7 8; 173 19 7 8; 174 20 7 8; 175 1 8 8; 176 2 8 8; 177 3 8 8; 178 4 8 8
34. 179 5 8 8; 180 6 8 8; 181 7 8 8; 182 8 8 8; 183 9 8 8; 184 10 8 8; 185 11 8 8
35. 186 12 8 8; 187 13 8 8; 188 14 8 8; 189 15 8 8; 190 16 8 8; 191 17 8 8
36. 192 18 8 8; 193 19 8 8; 194 19 0 0; 195 19 1 0; 196 20 1 0; 197 18 0 0
37. 198 18 1 0; 199 17 0 0; 200 17 1 0; 201 16 0 0; 202 16 1 0; 203 15 0 0
38. 204 15 1 0; 205 14 0 0; 206 14 1 0; 207 13 0 0; 208 13 1 0; 209 12 0 0

```

▲ STAAD SPACE -- PAGE NO. 2

```

39. 210 12 1 0; 211 11 0 0; 212 11 1 0; 213 10 0 0; 214 10 1 0; 215 9 0 0
40. 216 9 1 0; 217 8 0 0; 218 8 1 0; 219 7 0 0; 220 7 1 0; 221 6 0 0; 222 6 1 0
41. 223 5 0 0; 224 5 1 0; 225 4 0 0; 226 4 1 0; 227 3 0 0; 228 3 1 0; 229 2 0 0
42. 230 2 1 0; 231 1 0 0; 232 1 1 0; 233 0 1 0; 234 19 2 0; 235 20 2 0; 236 18 2 0
43. 237 17 2 0; 238 16 2 0; 239 15 2 0; 240 14 2 0; 241 13 2 0; 242 12 2 0
44. 243 11 2 0; 244 10 2 0; 245 9 2 0; 246 8 2 0; 247 7 2 0; 248 6 2 0; 249 5 2 0
45. 250 4 2 0; 251 3 2 0; 252 2 2 0; 253 1 2 0; 254 0 2 0; 255 19 3 0; 256 20 3 0
46. 257 18 3 0; 258 17 3 0; 259 16 3 0; 260 15 3 0; 261 14 3 0; 262 13 3 0
47. 263 12 3 0; 264 11 3 0; 265 10 3 0; 266 9 3 0; 267 8 3 0; 268 7 3 0; 269 6 3 0
48. 270 5 3 0; 271 4 3 0; 272 3 3 0; 273 2 3 0; 274 1 3 0; 275 0 3 0; 276 19 4 0
49. 277 20 4 0; 278 18 4 0; 279 17 4 0; 280 16 4 0; 281 15 4 0; 282 14 4 0
50. 283 13 4 0; 284 12 4 0; 285 11 4 0; 286 10 4 0; 287 9 4 0; 288 8 4 0
51. 289 7 4 0; 290 6 4 0; 291 5 4 0; 292 4 4 0; 293 3 4 0; 294 2 4 0; 295 1 4 0
52. 296 0 4 0; 297 19 5 0; 298 20 5 0; 299 18 5 0; 300 17 5 0; 301 16 5 0
53. 302 15 5 0; 303 14 5 0; 304 13 5 0; 305 12 5 0; 306 11 5 0; 307 10 5 0
54. 308 9 5 0; 309 8 5 0; 310 7 5 0; 311 6 5 0; 312 5 5 0; 313 4 5 0; 314 3 5 0
55. 315 2 5 0; 316 1 5 0; 317 0 5 0; 318 19 6 0; 319 20 6 0; 320 18 6 0
56. 321 17 6 0; 322 16 6 0; 323 15 6 0; 324 14 6 0; 325 13 6 0; 326 12 6 0
57. 327 11 6 0; 328 10 6 0; 329 9 6 0; 330 8 6 0; 331 7 6 0; 332 6 6 0; 333 5 6 0
58. 334 4 6 0; 335 3 6 0; 336 2 6 0; 337 1 6 0; 338 0 6 0; 339 19 7 0; 340 20 7 0
59. 341 18 7 0; 342 17 7 0; 343 16 7 0; 344 15 7 0; 345 14 7 0; 346 13 7 0
60. 347 12 7 0; 348 11 7 0; 349 10 7 0; 350 9 7 0; 351 8 7 0; 352 7 7 0; 353 6 7 0
61. 354 5 7 0; 355 4 7 0; 356 3 7 0; 357 2 7 0; 358 1 7 0; 359 0 7 0; 360 19 8 0
62. 361 18 8 0; 362 17 8 0; 363 16 8 0; 364 15 8 0; 365 14 8 0; 366 13 8 0
63. 367 12 8 0; 368 11 8 0; 369 10 8 0; 370 9 8 0; 371 8 8 0; 372 7 8 0; 373 6 8 0
64. 374 5 8 0; 375 4 8 0; 376 3 8 0; 377 2 8 0; 378 1 8 0; 379 0 0 1; 380 0 1 1

```

Staad Input Data.txt

65. 381 0 0 2; 382 0 1 2; 383 0 0 3; 384 0 1 3; 385 0 0 4; 386 0 1 4; 387 0 0 5
66. 388 0 1 5; 389 0 0 6; 390 0 1 6; 391 0 0 7; 392 0 1 7; 393 0 2 1; 394 0 2 2
67. 395 0 2 3; 396 0 2 4; 397 0 2 5; 398 0 2 6; 399 0 2 7; 400 0 3 1; 401 0 3 2
68. 402 0 3 3; 403 0 3 4; 404 0 3 5; 405 0 3 6; 406 0 3 7; 407 0 4 1; 408 0 4 2
69. 409 0 4 3; 410 0 4 4; 411 0 4 5; 412 0 4 6; 413 0 4 7; 414 0 5 1; 415 0 5 2
70. 416 0 5 3; 417 0 5 4; 418 0 5 5; 419 0 5 6; 420 0 5 7; 421 0 6 1; 422 0 6 2
71. 423 0 6 3; 424 0 6 4; 425 0 6 5; 426 0 6 6; 427 0 6 7; 428 0 7 1; 429 0 7 2
72. 430 0 7 3; 431 0 7 4; 432 0 7 5; 433 0 7 6; 434 0 7 7; 435 0 8 1; 436 0 8 2
73. 437 0 8 3; 438 0 8 4; 439 0 8 5; 440 0 8 6; 441 0 8 7; 442 20 0 7; 443 20 1 7
74. 444 20 0 6; 445 20 1 6; 446 20 0 5; 447 20 1 5; 448 20 0 4; 449 20 1 4
75. 450 20 0 3; 451 20 1 3; 452 20 0 2; 453 20 1 2; 454 20 0 1; 455 20 1 1
76. 456 20 2 7; 457 20 2 6; 458 20 2 5; 459 20 2 4; 460 20 2 3; 461 20 2 2
77. 462 20 2 1; 463 20 3 7; 464 20 3 6; 465 20 3 5; 466 20 3 4; 467 20 3 3
78. 468 20 3 2; 469 20 3 1; 470 20 4 7; 471 20 4 6; 472 20 4 5; 473 20 4 4
79. 474 20 4 3; 475 20 4 2; 476 20 4 1; 477 20 5 7; 478 20 5 6; 479 20 5 5
80. 480 20 5 4; 481 20 5 3; 482 20 5 2; 483 20 5 1; 484 20 6 7; 485 20 6 6
81. 486 20 6 5; 487 20 6 4; 488 20 6 3; 489 20 6 2; 490 20 6 1; 491 20 7 7
82. 492 20 7 6; 493 20 7 5; 494 20 7 4; 495 20 7 3; 496 20 7 2; 497 20 7 1
83. 498 20 8 7; 499 20 8 6; 500 20 8 5; 501 20 8 4; 502 20 8 3; 503 20 8 2
84. 504 20 8 1; 505 1 8 7; 506 2 8 7; 507 3 8 7; 508 4 8 7; 509 5 8 7; 510 6 8 7
85. 511 7 8 7; 512 8 8 7; 513 9 8 7; 514 10 8 7; 515 11 8 7; 516 12 8 7
86. 517 13 8 7; 518 14 8 7; 519 15 8 7; 520 16 8 7; 521 17 8 7; 522 18 8 7
87. 523 19 8 7; 524 1 8 6; 525 2 8 6; 526 3 8 6; 527 4 8 6; 528 5 8 6; 529 6 8 6
88. 530 7 8 6; 531 8 8 6; 532 9 8 6; 533 10 8 6; 534 11 8 6; 535 12 8 6
89. 536 13 8 6; 537 14 8 6; 538 15 8 6; 539 16 8 6; 540 17 8 6; 541 18 8 6
90. 542 19 8 6; 543 1 8 5; 544 2 8 5; 545 3 8 5; 546 4 8 5; 547 5 8 5; 548 6 8 5
91. 549 7 8 5; 550 8 8 5; 551 9 8 5; 552 10 8 5; 553 11 8 5; 554 12 8 5
92. 555 13 8 5; 556 14 8 5; 557 15 8 5; 558 16 8 5; 559 17 8 5; 560 18 8 5
93. 561 19 8 5; 562 1 8 4; 563 2 8 4; 564 3 8 4; 565 4 8 4; 566 5 8 4; 567 6 8 4
94. 568 7 8 4; 569 8 8 4; 570 9 8 4; 571 10 8 4; 572 11 8 4; 573 12 8 4
▲ STAAD SPACE -- PAGE NO. 3
95. 574 13 8 4; 575 14 8 4; 576 15 8 4; 577 16 8 4; 578 17 8 4; 579 18 8 4
96. 580 19 8 4; 581 1 8 3; 582 2 8 3; 583 3 8 3; 584 4 8 3; 585 5 8 3; 586 6 8 3
97. 587 7 8 3; 588 8 8 3; 589 9 8 3; 590 10 8 3; 591 11 8 3; 592 12 8 3
98. 593 13 8 3; 594 14 8 3; 595 15 8 3; 596 16 8 3; 597 17 8 3; 598 18 8 3
99. 599 19 8 3; 600 1 8 2; 601 2 8 2; 602 3 8 2; 603 4 8 2; 604 5 8 2; 605 6 8 2
100. 606 7 8 2; 607 8 8 2; 608 9 8 2; 609 10 8 2; 610 11 8 2; 611 12 8 2
101. 612 13 8 2; 613 14 8 2; 614 15 8 2; 615 16 8 2; 616 17 8 2; 617 18 8 2
102. 618 19 8 2; 619 1 8 1; 620 2 8 1; 621 3 8 1; 622 4 8 1; 623 5 8 1; 624 6 8 1
103. 625 7 8 1; 626 8 8 1; 627 9 8 1; 628 10 8 1; 629 11 8 1; 630 12 8 1
104. 631 13 8 1; 632 14 8 1; 633 15 8 1; 634 16 8 1; 635 17 8 1; 636 18 8 1
105. 637 19 8 1; 638 1 0 7; 639 2 0 7; 640 3 0 7; 641 4 0 7; 642 5 0 7; 643 6 0 7
106. 644 7 0 7; 645 8 0 7; 646 9 0 7; 647 10 0 7; 648 11 0 7; 649 12 0 7
107. 650 13 0 7; 651 14 0 7; 652 15 0 7; 653 16 0 7; 654 17 0 7; 655 18 0 7
108. 656 19 0 7; 657 1 0 6; 658 2 0 6; 659 3 0 6; 660 4 0 6; 661 5 0 6; 662 6 0 6
109. 663 7 0 6; 664 8 0 6; 665 9 0 6; 666 10 0 6; 667 11 0 6; 668 12 0 6
110. 669 13 0 6; 670 14 0 6; 671 15 0 6; 672 16 0 6; 673 17 0 6; 674 18 0 6
111. 675 19 0 6; 676 1 0 5; 677 2 0 5; 678 3 0 5; 679 4 0 5; 680 5 0 5; 681 6 0 5
112. 682 7 0 5; 683 8 0 5; 684 9 0 5; 685 10 0 5; 686 11 0 5; 687 12 0 5
113. 688 13 0 5; 689 14 0 5; 690 15 0 5; 691 16 0 5; 692 17 0 5; 693 18 0 5
114. 694 19 0 5; 695 1 0 4; 696 2 0 4; 697 3 0 4; 698 4 0 4; 699 5 0 4; 700 6 0 4
115. 701 7 0 4; 702 8 0 4; 703 9 0 4; 704 10 0 4; 705 11 0 4; 706 12 0 4
116. 707 13 0 4; 708 14 0 4; 709 15 0 4; 710 16 0 4; 711 17 0 4; 712 18 0 4
117. 713 19 0 4; 714 1 0 3; 715 2 0 3; 716 3 0 3; 717 4 0 3; 718 5 0 3; 719 6 0 3
118. 720 7 0 3; 721 8 0 3; 722 9 0 3; 723 10 0 3; 724 11 0 3; 725 12 0 3
119. 726 13 0 3; 727 14 0 3; 728 15 0 3; 729 16 0 3; 730 17 0 3; 731 18 0 3
120. 732 19 0 3; 733 1 0 2; 734 2 0 2; 735 3 0 2; 736 4 0 2; 737 5 0 2; 738 6 0 2
121. 739 7 0 2; 740 8 0 2; 741 9 0 2; 742 10 0 2; 743 11 0 2; 744 12 0 2
122. 745 13 0 2; 746 14 0 2; 747 15 0 2; 748 16 0 2; 749 17 0 2; 750 18 0 2
123. 751 19 0 2; 752 1 0 1; 753 2 0 1; 754 3 0 1; 755 4 0 1; 756 5 0 1; 757 6 0 1
124. 758 7 0 1; 759 8 0 1; 760 9 0 1; 761 10 0 1; 762 11 0 1; 763 12 0 1
125. 764 13 0 1; 765 14 0 1; 766 15 0 1; 767 16 0 1; 768 17 0 1; 769 18 0 1
126. 770 19 0 1; 771 0 -2 0; 772 0 -2 8; 773 20 -2 0; 774 20 -2 8
127. MEMBER INCIDENCES
128. 1 2 9; 2 1 231; 3 4 442; 4 2 391; 5 2 11; 6 1 233; 7 6 441; 8 6 175; 9 8 498
129. 10 5 378; 11 3 196; 12 4 48; 19 9 12; 20 11 50; 22 12 14; 24 14 16; 26 16 18
130. 28 18 20; 30 20 22; 32 22 24; 34 24 26; 36 26 28; 38 28 30; 40 30 32; 42 32 34
131. 44 34 36; 46 36 38; 48 38 40; 50 40 42; 52 42 44; 54 44 46; 56 46 48; 58 48 60
132. 60 50 71; 80 69 90; 82 71 92; 102 90 111; 104 92 113; 124 111 132; 126 113 134

Staad Input Data.txt

133. 146 132 153; 148 134 155; 168 153 174; 170 155 6; 190 174 8; 192 175 176
 134. 194 176 177; 196 177 178; 198 178 179; 200 179 180; 202 180 181; 204 181 182
 135. 206 182 183; 208 183 184; 210 184 185; 212 185 186; 214 186 187; 216 187 188
 136. 218 188 189; 220 189 190; 222 190 191; 224 191 192; 226 192 193; 228 193 8
 137. 231 194 3; 232 196 235; 234 197 194; 236 199 197; 238 201 199; 240 203 201
 138. 242 205 203; 244 207 205; 246 209 207; 248 211 209; 250 213 211; 252 215 213
 139. 254 217 215; 256 219 217; 258 221 219; 260 223 221; 262 225 223; 264 227 225
 140. 266 229 227; 268 231 229; 270 233 254; 272 235 256; 292 254 275; 294 256 277
 141. 314 275 296; 316 277 298; 336 296 317; 338 298 319; 358 317 338; 360 319 340
 142. 380 338 359; 382 340 7; 402 359 5; 404 360 7; 406 361 360; 408 362 361
 143. 410 363 362; 412 364 363; 414 365 364; 416 366 365; 418 367 366; 420 368 367
 144. 422 369 368; 424 370 369; 426 371 370; 428 372 371; 430 373 372; 432 374 373
 145. 434 375 374; 436 376 375; 438 377 376; 440 378 377; 443 379 1; 445 381 379
 146. 447 383 381; 449 385 383; 451 387 385; 453 389 387; 455 391 389; 506 435 5
 147. 508 436 435; 510 437 436; 512 438 437; 514 439 438; 516 440 439; 518 441 440
 148. 521 442 444; 523 444 446; 525 446 448; 527 448 450; 529 450 452; 531 452 454
 149. 533 454 3; 584 498 499; 586 499 500; 588 500 501; 590 501 502; 592 502 503
 150. 594 503 504; 596 504 7; 919 772 2; 920 771 1; 921 774 4; 922 773 3

STAAD SPACE

-- PAGE NO. 4

151. ELEMENT INCIDENCES SHELL

152. 21 2 9 10 11; 23 9 12 13 10; 25 12 14 15 13; 27 14 16 17 15; 29 16 18 19 17
 153. 31 18 20 21 19; 33 20 22 23 21; 35 22 24 25 23; 37 24 26 27 25; 39 26 28 29 27
 154. 41 28 30 31 29; 43 30 32 33 31; 45 32 34 35 33; 47 34 36 37 35; 49 36 38 39 37
 155. 51 38 40 41 39; 53 40 42 43 41; 55 42 44 45 43; 57 44 46 47 45; 59 46 4 48 47
 156. 61 11 10 49 50; 62 10 13 51 49; 63 13 15 52 51; 64 15 17 53 52; 65 17 19 54 53
 157. 66 19 21 55 54; 67 21 23 56 55; 68 23 25 57 56; 69 25 27 58 57; 70 27 29 59 58
 158. 71 29 31 60 59; 72 31 33 61 60; 73 33 35 62 61; 74 35 37 63 62; 75 37 39 64 63
 159. 76 39 41 65 64; 77 41 43 66 65; 78 43 45 67 66; 79 45 47 68 67; 81 47 48 69 68
 160. 83 50 49 70 71; 84 49 51 72 70; 85 51 52 73 72; 86 52 53 74 73; 87 53 54 75 74
 161. 88 54 55 76 75; 89 55 56 77 76; 90 56 57 78 77; 91 57 58 79 78; 92 58 59 80 79
 162. 93 59 60 81 80; 94 60 61 82 81; 95 61 62 83 82; 96 62 63 84 83; 97 63 64 85 84
 163. 98 64 65 86 85; 99 65 66 87 86; 100 66 67 88 87; 101 67 68 89 88
 164. 103 68 69 90 89; 105 71 70 91 92; 106 70 72 93 91; 107 72 73 94 93
 165. 108 73 74 95 94; 109 74 75 96 95; 110 75 76 97 96; 111 76 77 98 97
 166. 112 77 78 99 98; 113 78 79 100 99; 114 79 80 101 100; 115 80 81 102 101
 167. 116 81 82 103 102; 117 82 83 104 103; 118 83 84 105 104; 119 84 85 106 105
 168. 120 85 86 107 106; 121 86 87 108 107; 122 87 88 109 108; 123 88 89 110 109
 169. 125 89 90 111 110; 127 92 91 112 113; 128 91 93 114 112; 129 93 94 115 114
 170. 130 94 95 116 115; 131 95 96 117 116; 132 96 97 118 117; 133 97 98 119 118
 171. 134 98 99 120 119; 135 99 100 121 120; 136 100 101 122 121
 172. 137 101 102 123 122; 138 102 103 124 123; 139 103 104 125 124
 173. 140 104 105 126 125; 141 105 106 127 126; 142 106 107 128 127
 174. 143 107 108 129 128; 144 108 109 130 129; 145 109 110 131 130
 175. 147 110 111 132 131; 149 113 112 133 134; 150 112 114 135 133
 176. 151 114 115 136 135; 152 115 116 137 136; 153 116 117 138 137
 177. 154 117 118 139 138; 155 118 119 140 139; 156 119 120 141 140
 178. 157 120 121 142 141; 158 121 122 143 142; 159 122 123 144 143
 179. 160 123 124 145 144; 161 124 125 146 145; 162 125 126 147 146
 180. 163 126 127 148 147; 164 127 128 149 148; 165 128 129 150 149
 181. 166 129 130 151 150; 167 130 131 152 151; 169 131 132 153 152
 182. 171 134 133 154 155; 172 133 135 156 154; 173 135 136 157 156
 183. 174 136 137 158 157; 175 137 138 159 158; 176 138 139 160 159
 184. 177 139 140 161 160; 178 140 141 162 161; 179 141 142 163 162
 185. 180 142 143 164 163; 181 143 144 165 164; 182 144 145 166 165
 186. 183 145 146 167 166; 184 146 147 168 167; 185 147 148 169 168
 187. 186 148 149 170 169; 187 149 150 171 170; 188 150 151 172 171
 188. 189 151 152 173 172; 191 152 153 174 173; 193 155 154 175 6
 189. 195 154 156 176 175; 197 156 157 177 176; 199 157 158 178 177
 190. 201 158 159 179 178; 203 159 160 180 179; 205 160 161 181 180
 191. 207 161 162 182 181; 209 162 163 183 182; 211 163 164 184 183
 192. 213 164 165 185 184; 215 165 166 186 185; 217 166 167 187 186
 193. 219 167 168 188 187; 221 168 169 189 188; 223 169 170 190 189
 194. 225 170 171 191 190; 227 171 172 192 191; 229 172 173 193 192
 195. 230 173 174 8 193; 233 3 194 195 196; 235 194 197 198 195; 237 197 199 200 198
 196. 239 199 201 202 200; 241 201 203 204 202; 243 203 205 206 204
 197. 245 205 207 208 206; 247 207 209 210 208; 249 209 211 212 210
 198. 251 211 213 214 212; 253 213 215 216 214; 255 215 217 218 216
 199. 257 217 219 220 218; 259 219 221 222 220; 261 221 223 224 222
 200. 263 223 225 226 224; 265 225 227 228 226; 267 227 229 230 228

Staad Input Data.txt

201. 269 229 231 232 230; 271 231 1 233 232; 273 196 195 234 235
 202. 274 195 198 236 234; 275 198 200 237 236; 276 200 202 238 237
 203. 277 202 204 239 238; 278 204 206 240 239; 279 206 208 241 240
 204. 280 208 210 242 241; 281 210 212 243 242; 282 212 214 244 243
 205. 283 214 216 245 244; 284 216 218 246 245; 285 218 220 247 246
 206. 286 220 222 248 247; 287 222 224 249 248; 288 224 226 250 249

▲ STAAD SPACE -- PAGE NO. 5

207. 289 226 228 251 250; 290 228 230 252 251; 291 230 232 253 252
 208. 293 232 233 254 253; 295 235 234 255 256; 296 234 236 257 255
 209. 297 236 237 258 257; 298 237 238 259 258; 299 238 239 260 259
 210. 300 239 240 261 260; 301 240 241 262 261; 302 241 242 263 262
 211. 303 242 243 264 263; 304 243 244 265 264; 305 244 245 266 265
 212. 306 245 246 267 266; 307 246 247 268 267; 308 247 248 269 268
 213. 309 248 249 270 269; 310 249 250 271 270; 311 250 251 272 271
 214. 312 251 252 273 272; 313 252 253 274 273; 315 253 254 275 274
 215. 317 256 255 276 277; 318 255 257 278 276; 319 257 258 279 278
 216. 320 258 259 280 279; 321 259 260 281 280; 322 260 261 282 281
 217. 323 261 262 283 282; 324 262 263 284 283; 325 263 264 285 284
 218. 326 264 265 286 285; 327 265 266 287 286; 328 266 267 288 287
 219. 329 267 268 289 288; 330 268 269 290 289; 331 269 270 291 290
 220. 332 270 271 292 291; 333 271 272 293 292; 334 272 273 294 293
 221. 335 273 274 295 294; 337 274 275 296 295; 339 277 276 297 298
 222. 340 276 278 299 297; 341 278 279 300 299; 342 279 280 301 300
 223. 343 280 281 302 301; 344 281 282 303 302; 345 282 283 304 303
 224. 346 283 284 305 304; 347 284 285 306 305; 348 285 286 307 306
 225. 349 286 287 308 307; 350 287 288 309 308; 351 288 289 310 309
 226. 352 289 290 311 310; 353 290 291 312 311; 354 291 292 313 312
 227. 355 292 293 314 313; 356 293 294 315 314; 357 294 295 316 315
 228. 359 295 296 317 316; 361 298 297 318 319; 362 297 299 320 318
 229. 363 299 300 321 320; 364 300 301 322 321; 365 301 302 323 322
 230. 366 302 303 324 323; 367 303 304 325 324; 368 304 305 326 325
 231. 369 305 306 327 326; 370 306 307 328 327; 371 307 308 329 328
 232. 372 308 309 330 329; 373 309 310 331 330; 374 310 311 332 331
 233. 375 311 312 333 332; 376 312 313 334 333; 377 313 314 335 334
 234. 378 314 315 336 335; 379 315 316 337 336; 381 316 317 338 337
 235. 383 319 318 339 340; 384 318 320 341 339; 385 320 321 342 341
 236. 386 321 322 343 342; 387 322 323 344 343; 388 323 324 345 344
 237. 389 324 325 346 345; 390 325 326 347 346; 391 326 327 348 347
 238. 392 327 328 349 348; 393 328 329 350 349; 394 329 330 351 350
 239. 395 330 331 352 351; 396 331 332 353 352; 397 332 333 354 353
 240. 398 333 334 355 354; 399 334 335 356 355; 400 335 336 357 356
 241. 401 336 337 358 357; 403 337 338 359 358; 405 340 339 360 7
 242. 407 339 341 361 360; 409 341 342 362 361; 411 342 343 363 362
 243. 413 343 344 364 363; 415 344 345 365 364; 417 345 346 366 365
 244. 419 346 347 367 366; 421 347 348 368 367; 423 348 349 369 368
 245. 425 349 350 370 369; 427 350 351 371 370; 429 351 352 372 371
 246. 431 352 353 373 372; 433 353 354 374 373; 435 354 355 375 374
 247. 437 355 356 376 375; 439 356 357 377 376; 441 357 358 378 377
 248. 442 358 359 5 378; 444 1 379 380 233; 446 379 381 382 380; 448 381 383 384 382
 249. 450 383 385 386 384; 452 385 387 388 386; 454 387 389 390 388
 250. 456 389 391 392 390; 457 391 2 11 392; 458 233 380 393 254
 251. 459 380 382 394 393; 460 382 384 395 394; 461 384 386 396 395
 252. 462 386 388 397 396; 463 388 390 398 397; 464 390 392 399 398
 253. 465 392 11 50 399; 466 254 393 400 275; 467 393 394 401 400
 254. 468 394 395 402 401; 469 395 396 403 402; 470 396 397 404 403
 255. 471 397 398 405 404; 472 398 399 406 405; 473 399 50 71 406
 256. 474 275 400 407 296; 475 400 401 408 407; 476 401 402 409 408
 257. 477 402 403 410 409; 478 403 404 411 410; 479 404 405 412 411
 258. 480 405 406 413 412; 481 406 71 92 413; 482 296 407 414 317
 259. 483 407 408 415 414; 484 408 409 416 415; 485 409 410 417 416
 260. 486 410 411 418 417; 487 411 412 419 418; 488 412 413 420 419
 261. 489 413 92 113 420; 490 317 414 421 338; 491 414 415 422 421
 262. 492 415 416 423 422; 493 416 417 424 423; 494 417 418 425 424

▲ STAAD SPACE -- PAGE NO. 6

263. 495 418 419 426 425; 496 419 420 427 426; 497 420 113 134 427
 264. 498 338 421 428 359; 499 421 422 429 428; 500 422 423 430 429
 265. 501 423 424 431 430; 502 424 425 432 431; 503 425 426 433 432
 266. 504 426 427 434 433; 505 427 134 155 434; 507 359 428 435 5

Staad Input Data.txt

267. 509 428 429 436 435; 511 429 430 437 436; 513 430 431 438 437
 268. 515 431 432 439 438; 517 432 433 440 439; 519 433 434 441 440
 269. 520 434 155 6 441; 522 4 442 443 48; 524 442 444 445 443; 526 444 446 447 445
 270. 528 446 448 449 447; 530 448 450 451 449; 532 450 452 453 451
 271. 534 452 454 455 453; 535 454 3 196 455; 536 48 443 456 69; 537 443 445 457 456
 272. 538 445 447 458 457; 539 447 449 459 458; 540 449 451 460 459
 273. 541 451 453 461 460; 542 453 455 462 461; 543 455 196 235 462
 274. 544 69 456 463 90; 545 456 457 464 463; 546 457 458 465 464
 275. 547 458 459 466 465; 548 459 460 467 466; 549 460 461 468 467
 276. 550 461 462 469 468; 551 462 235 256 469; 552 90 463 470 111
 277. 553 463 464 471 470; 554 464 465 472 471; 555 465 466 473 472
 278. 556 466 467 474 473; 557 467 468 475 474; 558 468 469 476 475
 279. 559 469 256 277 476; 560 111 470 477 132; 561 470 471 478 477
 280. 562 471 472 479 478; 563 472 473 480 479; 564 473 474 481 480
 281. 565 474 475 482 481; 566 475 476 483 482; 567 476 277 298 483
 282. 568 132 477 484 153; 569 477 478 485 484; 570 478 479 486 485
 283. 571 479 480 487 486; 572 480 481 488 487; 573 481 482 489 488
 284. 574 482 483 490 489; 575 483 298 319 490; 576 153 484 491 174
 285. 577 484 485 492 491; 578 485 486 493 492; 579 486 487 494 493
 286. 580 487 488 495 494; 581 488 489 496 495; 582 489 490 497 496
 287. 583 490 319 340 497; 585 174 491 498 8; 587 491 492 499 498
 288. 589 492 493 500 499; 591 493 494 501 500; 593 494 495 502 501
 289. 595 495 496 503 502; 597 496 497 504 503; 598 497 340 7 504; 599 6 175 505 441
 290. 600 175 176 506 505; 601 176 177 507 506; 602 177 178 508 507
 291. 603 178 179 509 508; 604 179 180 510 509; 605 180 181 511 510
 292. 606 181 182 512 511; 607 182 183 513 512; 608 183 184 514 513
 293. 609 184 185 515 514; 610 185 186 516 515; 611 186 187 517 516
 294. 612 187 188 518 517; 613 188 189 519 518; 614 189 190 520 519
 295. 615 190 191 521 520; 616 191 192 522 521; 617 192 193 523 522
 296. 618 193 8 498 523; 619 441 505 524 440; 620 505 506 525 524
 297. 621 506 507 526 525; 622 507 508 527 526; 623 508 509 528 527
 298. 624 509 510 529 528; 625 510 511 530 529; 626 511 512 531 530
 299. 627 512 513 532 531; 628 513 514 533 532; 629 514 515 534 533
 300. 630 515 516 535 534; 631 516 517 536 535; 632 517 518 537 536
 301. 633 518 519 538 537; 634 519 520 539 538; 635 520 521 540 539
 302. 636 521 522 541 540; 637 522 523 542 541; 638 523 498 499 542
 303. 639 440 524 543 439; 640 524 525 544 543; 641 525 526 545 544
 304. 642 526 527 546 545; 643 527 528 547 546; 644 528 529 548 547
 305. 645 529 530 549 548; 646 530 531 550 549; 647 531 532 551 550
 306. 648 532 533 552 551; 649 533 534 553 552; 650 534 535 554 553
 307. 651 535 536 555 554; 652 536 537 556 555; 653 537 538 557 556
 308. 654 538 539 558 557; 655 539 540 559 558; 656 540 541 560 559
 309. 657 541 542 561 560; 658 542 499 500 561; 659 439 543 562 438
 310. 660 543 544 563 562; 661 544 545 564 563; 662 545 546 565 564
 311. 663 546 547 566 565; 664 547 548 567 566; 665 548 549 568 567
 312. 666 549 550 569 568; 667 550 551 570 569; 668 551 552 571 570
 313. 669 552 553 572 571; 670 553 554 573 572; 671 554 555 574 573
 314. 672 555 556 575 574; 673 556 557 576 575; 674 557 558 577 576
 315. 675 558 559 578 577; 676 559 560 579 578; 677 560 561 580 579
 316. 678 561 500 501 580; 679 438 562 581 437; 680 562 563 582 581
 317. 681 563 564 583 582; 682 564 565 584 583; 683 565 566 585 584
 318. 684 566 567 586 585; 685 567 568 587 586; 686 568 569 588 587

▲ STAAD SPACE -- PAGE NO. 7

319. 687 569 570 589 588; 688 570 571 590 589; 689 571 572 591 590
 320. 690 572 573 592 591; 691 573 574 593 592; 692 574 575 594 593
 321. 693 575 576 595 594; 694 576 577 596 595; 695 577 578 597 596
 322. 696 578 579 598 597; 697 579 580 599 598; 698 580 501 502 599
 323. 699 437 581 600 436; 700 581 582 601 600; 701 582 583 602 601
 324. 702 583 584 603 602; 703 584 585 604 603; 704 585 586 605 604
 325. 705 586 587 606 605; 706 587 588 607 606; 707 588 589 608 607
 326. 708 589 590 609 608; 709 590 591 610 609; 710 591 592 611 610
 327. 711 592 593 612 611; 712 593 594 613 612; 713 594 595 614 613
 328. 714 595 596 615 614; 715 596 597 616 615; 716 597 598 617 616
 329. 717 598 599 618 617; 718 599 502 503 618; 719 436 600 619 435
 330. 720 600 601 620 619; 721 601 602 621 620; 722 602 603 622 621
 331. 723 603 604 623 622; 724 604 605 624 623; 725 605 606 625 624
 332. 726 606 607 626 625; 727 607 608 627 626; 728 608 609 628 627
 333. 729 609 610 629 628; 730 610 611 630 629; 731 611 612 631 630
 334. 732 612 613 632 631; 733 613 614 633 632; 734 614 615 634 633

Staad Input Data.txt

335. 735 615 616 635 634; 736 616 617 636 635; 737 617 618 637 636
336. 738 618 503 504 637; 739 435 619 378 5; 740 619 620 377 378
337. 741 620 621 376 377; 742 621 622 375 376; 743 622 623 374 375
338. 744 623 624 373 374; 745 624 625 372 373; 746 625 626 371 372
339. 747 626 627 370 371; 748 627 628 369 370; 749 628 629 368 369
340. 750 629 630 367 368; 751 630 631 366 367; 752 631 632 365 366
341. 753 632 633 364 365; 754 633 634 363 364; 755 634 635 362 363
342. 756 635 636 361 362; 757 636 637 360 361; 758 637 504 7 360; 759 2 9 638 391
343. 760 9 12 639 638; 761 12 14 640 639; 762 14 16 641 640; 763 16 18 642 641
344. 764 18 20 643 642; 765 20 22 644 643; 766 22 24 645 644; 767 24 26 646 645
345. 768 26 28 647 646; 769 28 30 648 647; 770 30 32 649 648; 771 32 34 650 649
346. 772 34 36 651 650; 773 36 38 652 651; 774 38 40 653 652; 775 40 42 654 653
347. 776 42 44 655 654; 777 44 46 656 655; 778 46 4 442 656; 779 391 638 657 389
348. 780 638 639 658 657; 781 639 640 659 658; 782 640 641 660 659
349. 783 641 642 661 660; 784 642 643 662 661; 785 643 644 663 662
350. 786 644 645 664 663; 787 645 646 665 664; 788 646 647 666 665
351. 789 647 648 667 666; 790 648 649 668 667; 791 649 650 669 668
352. 792 650 651 670 669; 793 651 652 671 670; 794 652 653 672 671
353. 795 653 654 673 672; 796 654 655 674 673; 797 655 656 675 674
354. 798 656 442 444 675; 799 389 657 676 387; 800 657 658 677 676
355. 801 658 659 678 677; 802 659 660 679 678; 803 660 661 680 679
356. 804 661 662 681 680; 805 662 663 682 681; 806 663 664 683 682
357. 807 664 665 684 683; 808 665 666 685 684; 809 666 667 686 685
358. 810 667 668 687 686; 811 668 669 688 687; 812 669 670 689 688
359. 813 670 671 690 689; 814 671 672 691 690; 815 672 673 692 691
360. 816 673 674 693 692; 817 674 675 694 693; 818 675 444 446 694
361. 819 387 676 695 385; 820 676 677 696 695; 821 677 678 697 696
362. 822 678 679 698 697; 823 679 680 699 698; 824 680 681 700 699
363. 825 681 682 701 700; 826 682 683 702 701; 827 683 684 703 702
364. 828 684 685 704 703; 829 685 686 705 704; 830 686 687 706 705
365. 831 687 688 707 706; 832 688 689 708 707; 833 689 690 709 708
366. 834 690 691 710 709; 835 691 692 711 710; 836 692 693 712 711
367. 837 693 694 713 712; 838 694 446 448 713; 839 385 695 714 383
368. 840 695 696 715 714; 841 696 697 716 715; 842 697 698 717 716
369. 843 698 699 718 717; 844 699 700 719 718; 845 700 701 720 719
370. 846 701 702 721 720; 847 702 703 722 721; 848 703 704 723 722
371. 849 704 705 724 723; 850 705 706 725 724; 851 706 707 726 725
372. 852 707 708 727 726; 853 708 709 728 727; 854 709 710 729 728
373. 855 710 711 730 729; 856 711 712 731 730; 857 712 713 732 731
374. 858 713 448 450 732; 859 383 714 733 381; 860 714 715 734 733

▲ STAAD SPACE -- PAGE NO. 8

375. 861 715 716 735 734; 862 716 717 736 735; 863 717 718 737 736
376. 864 718 719 738 737; 865 719 720 739 738; 866 720 721 740 739
377. 867 721 722 741 740; 868 722 723 742 741; 869 723 724 743 742
378. 870 724 725 744 743; 871 725 726 745 744; 872 726 727 746 745
379. 873 727 728 747 746; 874 728 729 748 747; 875 729 730 749 748
380. 876 730 731 750 749; 877 731 732 751 750; 878 732 450 452 751
381. 879 381 733 752 379; 880 733 734 753 752; 881 734 735 754 753
382. 882 735 736 755 754; 883 736 737 756 755; 884 737 738 757 756
383. 885 738 739 758 757; 886 739 740 759 758; 887 740 741 760 759
384. 888 741 742 761 760; 889 742 743 762 761; 890 743 744 763 762
385. 891 744 745 764 763; 892 745 746 765 764; 893 746 747 766 765
386. 894 747 748 767 766; 895 748 749 768 767; 896 749 750 769 768
387. 897 750 751 770 769; 898 751 452 454 770; 899 379 752 231 1
388. 900 752 753 229 231; 901 753 754 227 229; 902 754 755 225 227
389. 903 755 756 223 225; 904 756 757 221 223; 905 757 758 219 221
390. 906 758 759 217 219; 907 759 760 215 217; 908 760 761 213 215
391. 909 761 762 211 213; 910 762 763 209 211; 911 763 764 207 209
392. 912 764 765 205 207; 913 765 766 203 205; 914 766 767 201 203
393. 915 767 768 199 201; 916 768 769 197 199; 917 769 770 194 197
394. 918 770 454 3 194
395. DEFINE PMEMBER
396. 1 19 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50 52 54 56 PMEMBER 1
397. 2 268 266 264 262 260 258 256 254 252 250 248 246 244 242 240 238 236 234 -
398. 231 PMEMBER 2
399. 8 192 194 196 198 200 202 204 206 208 210 212 214 216 218 220 222 224 226 -
400. 228 PMEMBER 3
401. 10 440 438 436 434 432 430 428 426 424 422 420 418 416 414 412 410 408 406 -
402. 404 PMEMBER 4

Staad Input Data.txt

```

403. 4 455 453 451 449 447 445 443 PMEMBER 5
404. 7 518 516 514 512 510 508 506 PMEMBER 6
405. 3 521 523 525 527 529 531 533 PMEMBER 7
406. 9 584 586 588 590 592 594 596 PMEMBER 8
407. 6 270 292 314 336 358 380 402 PMEMBER 9
408. 5 20 60 82 104 126 148 170 PMEMBER 10
409. 12 58 80 102 124 146 168 190 PMEMBER 11
410. 11 232 272 294 316 338 360 382 PMEMBER 12
411. START GROUP DEFINITION
412. MEMBER
413. _EB 1 TO 10 12 56 170 190 228 382 402 404 443 506 596
414. _CC 919 TO 922
415. _SCB 11 19 20 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50 52 54 58 60 80 -
416. 82 102 104 124 126 146 148 168 192 194 196 198 200 202 204 206 208 210 212 -
417. 214 216 218 220 222 224 226 231 232 234 236 238 240 242 244 246 248 250 252 -
418. 254 256 258 260 262 264 266 268 270 272 292 294 314 316 336 338 358 360 380 -
419. 406 408 410 412 414 416 418 420 422 424 426 428 430 432 434 436 438 440 445 -
420. 447 449 451 453 455 508 510 512 514 516 518 521 523 525 527 529 531 533 584 -
421. 586 588 590 592 594
422. END GROUP DEFINITION
423. ELEMENT PROPERTY
424. 21 23 25 27 29 31 33 35 37 39 41 43 45 47 49 51 53 55 57 59 61 TO 79 81 83 -
425. 84 TO 101 103 105 TO 123 125 127 TO 145 147 149 TO 167 169 171 TO 189 191 -
426. 193 195 197 199 201 203 205 207 209 211 213 215 217 219 221 223 225 227 229 -
427. 230 233 235 237 239 241 243 245 247 249 251 253 255 257 259 261 263 265 267 -
428. 269 271 273 TO 291 293 295 TO 313 315 317 TO 335 337 339 TO 357 359 -
429. 361 TO 379 381 383 TO 401 403 405 407 409 411 413 415 417 419 421 423 425 -
430. 427 429 431 433 435 437 439 441 442 444 446 448 450 452 454 456 TO 505 507 -
  STAAD SPACE -- PAGE NO. 9

431. 509 511 513 515 517 519 520 522 524 526 528 530 532 534 TO 583 585 587 589 -
432. 591 593 595 597 TO 918 THICKNESS 0.021
433. DEFINE MATERIAL START
434. ISOTROPIC STEEL
435. E 4.176E+006
436. POISSON 0.3
437. DENSITY 0.489024
438. ALPHA 6E-006
439. DAMP 0.03
440. TYPE STEEL
441. STRENGTH FY 5184 FU 8352 RY 1.5 RT 1.2
442. ISOTROPIC CONCRETE
443. E 453600
444. POISSON 0.17
445. DENSITY 0.150336
446. ALPHA 5E-006
447. DAMP 0.05
448. TYPE CONCRETE
449. STRENGTH FCU 576
450. END DEFINE MATERIAL
451. MEMBER PROPERTY AMERICAN
452. _SCB TABLE ST HSST2.5X2.5X0.125
453. _EB TABLE ST HSST3.5X3.5X0.188
454. MEMBER PROPERTY AMERICAN
455. _CC PRIS YD 1 ZD 1
456. CONSTANTS
457. MATERIAL STEEL MEMB 1 TO 12 19 TO 918
458. MATERIAL CONCRETE MEMB 919 TO 922
459. SUPPORTS
460. 771 TO 774 PINNED
461. DEFINE IBC 2012
462. ZIP 94116 I 1 RX 8 RZ 8 SCLASS 4 TL 8 FA 1 FV 1.5

```

```

*****
* EQUIV. SEISMIC LOADS AS PER IBC 2012 *
* PARAMETERS CONSIDERED FOR SUBSEQUENT LOAD GENERATION *
* SS = 2.071 S1 = 0.980 FA = 1.000 FV = 1.500 *
* SDS = 1.381 SD1 = 0.980 *
*****

```

463. SELFWEIGHT 1
464. ELEMENT WEIGHT
465. 759 TO 918 PRESSURE 0.05
466. DEFINE WIND LOAD

*** NOTE: If any floor diaphragm is present in the model Wind Load definition should be defined after Floor Diaphragm definition. Otherwise wind load generation may be unsuccessful during analysis.

467. TYPE 1 WIND 1
468. <! STAAD PRO GENERATED DATA DO NOT MODIFY !!!
469. ASCE-7-2010:PARAMS 180.000 MPH 0 3 1 0 0.000 FT 0.000 FT 0.000 FT 1 -
470. 1 8.000 FT 20.000 FT 8.000 FT 2.000 0.010 0 -
471. 0 0 0 0 1.030 1.000 1.000 0.850 0 -
472. 0 0 0 0.907 0.800 -0.550

STAAD SPACE

-- PAGE NO. 10

473. !> END GENERATED DATA BLOCK
474. INT 0.0926768 0.0926768 HEIG 0 15
475. EXP 0.85 JOINT 1 TO 774
476. TYPE 2 WIND 2
477. <! STAAD PRO GENERATED DATA DO NOT MODIFY !!!
478. ASCE-7-2010:PARAMS 180.000 MPH 0 3 1 0 0.000 FT 0.000 FT 0.000 FT 1 -
479. 1 8.000 FT 20.000 FT 8.000 FT 2.000 0.010 0 -
480. 0 0 0 0 1.030 1.000 1.000 0.850 0 -
481. 0 0 0 0.907 0.800 -0.550
482. !> END GENERATED DATA BLOCK
483. INT 0.0926768 0.0926768 HEIG 0 15
484. EXP 0.85 JOINT 1 TO 774
485. DEFINE REFERENCE LOADS
486. LOAD R1 LOADTYPE DEAD TITLE REF LOAD CASE 1
487. SELFWEIGHT Y -1
488. END DEFINE REFERENCE LOADS
489. LOAD 1 LOADTYPE SEISMIC TITLE EQX
490. IBC LOAD X 1
491. PERFORM ANALYSIS

P R O B L E M S T A T I S T I C S

NUMBER OF JOINTS	774	NUMBER OF MEMBERS	148
NUMBER OF PLATES	768	NUMBER OF SOLIDS	0
NUMBER OF SURFACES	0	NUMBER OF SUPPORTS	4

SOLVER USED IS THE IN-CORE ADVANCED MATH SOLVER

TOTAL PRIMARY LOAD CASES = 1, TOTAL DEGREES OF FREEDOM = 4632
TOTAL LOAD COMBINATION CASES = 0 SO FAR.

STAAD SPACE

-- PAGE NO. 11

* IBC 2012 SEISMIC LOAD ALONG X : *
* CT = 0.028 Cu = 1.400 x = 0.8000 *
* TIME PERIODS : *
* Ta = 0.177 T = 0.082 Tuser = 0.000 *
* TIME PERIOD USED (T) = 0.082 *
* Cs LIMITS : LOWER = 0.061 UPPER = 1.486 *
* LOAD FACTOR = 1.000 *
* DESIGN BASE SHEAR = 1.000 X 0.173 X 17.70 *
* = 3.05 KIP *

492. CHANGE
 493. LOAD 2 LOADTYPE SEISMIC TITLE EQZ
 494. IBC LOAD Z 1
 495. PERFORM ANALYSIS

```
*****
*   IBC 2012 SEISMIC LOAD ALONG Z   :   *
*   CT = 0.028 Cu = 1.400 x = 0.8000   *
*   TIME PERIODS :                     *
*   Ta = 0.177 T = 0.155 Tuser = 0.000   *
*   TIME PERIOD USED (T) = 0.155         *
*   Cs LIMITS : LOWER = 0.061 UPPER = 0.792   *
*   LOAD FACTOR      = 1.000             *
*   DESIGN BASE SHEAR = 1.000 X 0.173 X 17.70 *
*                               = 3.05 KIP      *
*****
```

496. CHANGE
 497. LOAD 3 LOADTYPE DEAD TITLE DEAD LOAD
 498. ELEMENT LOAD
 499. 759 TO 918 PR GY -0.05
 500. SELFWEIGHT Y -1
 501. LOAD 4 LOADTYPE ROOF LIVE TITLE ROOF LIVE
 502. ELEMENT LOAD
 503. 599 TO 758 PR GY -0.3
 504. LOAD 5 LOADTYPE WIND TITLE WIND_X
 505. WIND LOAD X 1 TYPE 1 YR 0 8 ZR 0 8



STAAD SPACE

-- PAGE NO. 12

506. LOAD 6 LOADTYPE WIND TITLE WIND_Z
 507. WIND LOAD Z 1 TYPE 2 YR 0 8 ZR 0 20
 508. LOAD COMB 7 GENERATED AISC GENERAL 1
 509. 3 1.0
 510. LOAD COMB 8 GENERATED AISC GENERAL 2
 511. 3 1.0 4 1.0
 512. LOAD COMB 9 GENERATED AISC GENERAL 3
 513. 3 1.0 4 0.75
 514. LOAD COMB 10 GENERATED AISC GENERAL 4
 515. 3 1.0 5 1.0
 516. LOAD COMB 11 GENERATED AISC GENERAL 5
 517. 3 1.0 6 1.0
 518. LOAD COMB 12 GENERATED AISC GENERAL 6
 519. 3 1.0 1 0.7
 520. LOAD COMB 13 GENERATED AISC GENERAL 7
 521. 3 1.0 2 0.7
 522. LOAD COMB 14 GENERATED AISC GENERAL 8
 523. 3 1.0 1 -0.7
 524. LOAD COMB 15 GENERATED AISC GENERAL 9
 525. 3 1.0 2 -0.7
 526. LOAD COMB 16 GENERATED AISC GENERAL 10
 527. 3 1.0 4 0.75 5 0.75
 528. LOAD COMB 17 GENERATED AISC GENERAL 11
 529. 3 1.0 4 0.75 6 0.75
 530. LOAD COMB 18 GENERATED AISC GENERAL 12
 531. 3 1.0 5 0.75
 532. LOAD COMB 19 GENERATED AISC GENERAL 13
 533. 3 1.0 6 0.75
 534. LOAD COMB 20 GENERATED AISC GENERAL 14
 535. 3 1.0 4 0.75 1 0.525
 536. LOAD COMB 21 GENERATED AISC GENERAL 15
 537. 3 1.0 4 0.75 2 0.525
 538. LOAD COMB 22 GENERATED AISC GENERAL 16

539. 3 1.0 1 0.525
 540. LOAD COMB 23 GENERATED AISC GENERAL 17
 541. 3 1.0 2 0.525
 542. LOAD COMB 24 GENERATED AISC GENERAL 18
 543. 3 1.0 4 0.75 1 -0.525
 544. LOAD COMB 25 GENERATED AISC GENERAL 19
 545. 3 1.0 4 0.75 2 -0.525
 546. LOAD COMB 26 GENERATED AISC GENERAL 20
 547. 3 1.0 1 -0.525
 548. LOAD COMB 27 GENERATED AISC GENERAL 21
 549. 3 1.0 2 -0.525
 550. LOAD COMB 28 GENERATED AISC GENERAL 22
 551. 3 0.6 5 1.0
 552. LOAD COMB 29 GENERATED AISC GENERAL 23
 553. 3 0.6 6 1.0
 554. LOAD COMB 30 GENERATED AISC GENERAL 24
 555. 3 0.6 1 0.7

▲ STAAD SPACE

-- PAGE NO. 13

556. LOAD COMB 31 GENERATED AISC GENERAL 25
 557. 3 0.6 2 0.7
 558. LOAD COMB 32 GENERATED AISC GENERAL 26
 559. 3 0.6 1 -0.7
 560. LOAD COMB 33 GENERATED AISC GENERAL 27
 561. 3 0.6 2 -0.7
 562. LOAD COMB 34 GENERATED ACI TABLE1 1
 563. 3 1.4
 564. LOAD COMB 35 GENERATED ACI TABLE1 2
 565. 3 1.2 4 0.5
 566. LOAD COMB 36 GENERATED ACI TABLE1 3
 567. 3 1.2
 568. LOAD COMB 37 GENERATED ACI TABLE1 4
 569. 3 1.2 4 1.6
 570. LOAD COMB 38 GENERATED ACI TABLE1 5
 571. 3 1.2 4 1.6 5 0.8
 572. LOAD COMB 39 GENERATED ACI TABLE1 6
 573. 3 1.2 4 1.6 6 0.8
 574. LOAD COMB 40 GENERATED ACI TABLE1 7
 575. 3 1.2 5 0.8
 576. LOAD COMB 41 GENERATED ACI TABLE1 8
 577. 3 1.2 6 0.8
 578. LOAD COMB 42 GENERATED ACI TABLE1 9
 579. 3 1.2 4 0.5 5 1.6
 580. LOAD COMB 43 GENERATED ACI TABLE1 10
 581. 3 1.2 4 0.5 6 1.6
 582. LOAD COMB 44 GENERATED ACI TABLE1 11
 583. 3 1.2 5 1.6
 584. LOAD COMB 45 GENERATED ACI TABLE1 12
 585. 3 1.2 6 1.6
 586. LOAD COMB 46 GENERATED ACI TABLE1 13
 587. 3 1.2 1 1.0
 588. LOAD COMB 47 GENERATED ACI TABLE1 14
 589. 3 1.2 2 1.0
 590. LOAD COMB 48 GENERATED ACI TABLE1 15
 591. 3 0.9 5 1.6
 592. LOAD COMB 49 GENERATED ACI TABLE1 16
 593. 3 0.9 6 1.6
 594. LOAD COMB 50 GENERATED ACI TABLE1 17
 595. 3 0.9 1 1.0
 596. LOAD COMB 51 GENERATED ACI TABLE1 18
 597. 3 0.9 2 1.0
 598. PERFORM ANALYSIS

599. LOAD LIST 7 TO 33
 600. PARAMETER 1
 601. CODE AISC
 602. TRACK 2 MEMB 1 TO 12 19 20 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50 52 -
 603. 54 56 58 60 80 82 102 104 124 126 146 148 168 170 190 192 194 196 198 200 -
 604. 202 204 206 208 210 212 214 216 218 220 222 224 226 228 231 232 234 236 238 -

Staad Input Data.txt

```

605. 240 242 244 246 248 250 252 254 256 258 260 262 264 266 268 270 272 292 294 -
606. 314 316 336 338 358 360 380 382 402 404 406 408 410 412 414 416 418 420 422 -
^   STAAD SPACE                                     -- PAGE NO.   14

607. 424 426 428 430 432 434 436 438 440 443 445 447 449 451 453 455 506 508 510 -
608. 512 514 516 518 521 523 525 527 529 531 533 584 586 588 590 592 594 596
609. RATIO 1.05 ALL
610. CHECK CODE MEMB 1 TO 12 19 20 22 24 26 28 30 32 34 36 38 40 42 44 46 48 50 -
611. 52 54 56 58 60 80 82 102 104 124 126 146 148 168 170 190 192 194 196 198 -
612. 200 202 204 206 208 210 212 214 216 218 220 222 224 226 228 231 232 234 236 -
613. 238 240 242 244 246 248 250 252 254 256 258 260 262 264 266 268 270 272 292 -
614. 294 314 316 336 338 358 360 380 382 402 404 406 408 410 412 414 416 418 420 -
615. 422 424 426 428 430 432 434 436 438 440 443 445 447 449 451 453 455 506 508 -
616. 510 512 514 516 518 521 523 525 527 529 531 533 584 586 588 590 592 594 596

^   STAAD SPACE                                     -- PAGE NO.  303

617. LOAD LIST 34 TO 51
618. START CONCRETE DESIGN
^   STAAD SPACE                                     -- PAGE NO.  304

[CONCRETE DESIGN]
619. CODE ACI
620. TRACK 2 MEMB 919 TO 922
621. DESIGN COLUMN 919 TO 922
^   STAAD SPACE                                     -- PAGE NO.  305

```

ACI 318-11 COLUMN NO. 919 DESIGN RESULTS
=====

[]

FY - 60000 FC - 4000 PSI, SQRE SIZE - 12.00 X 12.00 INCHES, TIED
ONLY MINIMUM STEEL IS REQUIRED.
AREA OF STEEL REQUIRED = 1.440 SQ. IN.

BAR CONFIGURATION	REINF PCT.	LOAD	LOCATION	PHI
<hr/>				
8 - NUMBER 4	1.111	34	END	0.650
(PROVIDE EQUAL NUMBER OF BARS ON EACH FACE)				
TIE BAR NUMBER 4 SPACING 8.00 IN				

COLUMN INTERACTION: MOMENT ABOUT Z -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	8.75	1.60	0.09164

COLUMN INTERACTION: MOMENT ABOUT Y -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	8.75	2.82	0.16101

		Pn	Mn	Pn	Mn	(@ Z)
		428.43	54.43	214.21	84.42	
P0	*	392.72	62.91	178.51	82.09	
	*	357.02	69.84	142.81	77.19	
Pn,max	*	321.32	75.23	107.11	71.14	
	*	285.62	79.28	71.40	62.97	
Pn	*	249.92	82.26	35.70	51.70	
NOMINAL	*	Pn	Mn	Pn	Mn	(@ Y)

Staad Input Data.txt					
AXIAL	*	428.43	54.43	214.21	84.42
COMPRESSION	*	392.72	62.91	178.51	82.09
Pb	-----*Mb	357.02	69.84	142.81	77.19
	*	321.32	75.23	107.11	71.14
	*	285.62	79.28	71.40	62.97
	* M0 Mn,	249.92	82.26	35.70	51.70
	* BENDING				
P-tens	* MOMENT				
STAAD SPACE					-- PAGE NO. 306

ACI 318-11 COLUMN NO. 920 DESIGN RESULTS
=====

FY - 60000 FC - 4000 PSI, SQRE SIZE - 12.00 X 12.00 INCHES, TIED
ONLY MINIMUM STEEL IS REQUIRED.
AREA OF STEEL REQUIRED = 1.440 SQ. IN.

BAR CONFIGURATION	REINF PCT.	LOAD	LOCATION	PHI
8 - NUMBER 4	1.111	34	END	0.650

(PROVIDE EQUAL NUMBER OF BARS ON EACH FACE)
TIE BAR NUMBER 4 SPACING 8.00 IN

COLUMN INTERACTION: MOMENT ABOUT Z -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	9.03	1.69	0.09362

COLUMN INTERACTION: MOMENT ABOUT Y -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	9.03	2.93	0.16245

		Pn	Mn	Pn	Mn	(@ Z)
		428.43	54.43	214.21	84.42	
P0	*	392.72	62.91	178.51	82.09	
	*	357.02	69.84	142.81	77.19	
Pn,max	*	321.32	75.23	107.11	71.14	
	*	285.62	79.28	71.40	62.97	
Pn	*	249.92	82.26	35.70	51.70	
NOMINAL	*	Pn	Mn	Pn	Mn	(@ Y)
AXIAL	*	428.43	54.43	214.21	84.42	
COMPRESSION	*	392.72	62.91	178.51	82.09	
Pb	-----*Mb	357.02	69.84	142.81	77.19	
	*	321.32	75.23	107.11	71.14	
	*	285.62	79.28	71.40	62.97	
	* M0 Mn,	249.92	82.26	35.70	51.70	
	* BENDING					
P-tens	* MOMENT					
STAAD SPACE						-- PAGE NO. 307

ACI 318-11 COLUMN NO. 921 DESIGN RESULTS
=====

□

FY - 60000 FC - 4000 PSI, SQRE SIZE - 12.00 X 12.00 INCHES, TIED
ONLY MINIMUM STEEL IS REQUIRED.
AREA OF STEEL REQUIRED = 1.440 SQ. IN.

BAR CONFIGURATION REINF PCT. LOAD LOCATION PHI

8 - NUMBER 4 1.111 34 END 0.650
(PROVIDE EQUAL NUMBER OF BARS ON EACH FACE)
TIE BAR NUMBER 4 SPACING 8.00 IN

COLUMN INTERACTION: MOMENT ABOUT Z -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	9.03	1.89	0.10479

COLUMN INTERACTION: MOMENT ABOUT Y -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	9.03	2.68	0.14867

		Pn	Mn	Pn	Mn	(@ Z)
P0	*	428.43	54.43	214.21	84.42	
	*	392.72	62.91	178.51	82.09	
Pn,max	*	357.02	69.84	142.81	77.19	
	*	321.32	75.23	107.11	71.14	
Pn	*	285.62	79.28	71.40	62.97	
NOMINAL	*	249.92	82.26	35.70	51.70	
AXIAL	*	Pn	Mn	Pn	Mn	(@ Y)
COMPRESSION	*	428.43	54.43	214.21	84.42	
	*	392.72	62.91	178.51	82.09	
Pb	-----*Mb	357.02	69.84	142.81	77.19	
	*	321.32	75.23	107.11	71.14	
	*	285.62	79.28	71.40	62.97	
	* M0 Mn,	249.92	82.26	35.70	51.70	
	* BENDING					
P-tens	*					
	* MOMENT					

↑ STAAD SPACE

-- PAGE NO. 308

ACI 318-11 COLUMN NO. 922 DESIGN RESULTS
=====

□

FY - 60000 FC - 4000 PSI, SQRE SIZE - 12.00 X 12.00 INCHES, TIED
ONLY MINIMUM STEEL IS REQUIRED.
AREA OF STEEL REQUIRED = 1.440 SQ. IN.

BAR CONFIGURATION REINF PCT. LOAD LOCATION PHI

8 - NUMBER 4 1.111 34 END 0.650
(PROVIDE EQUAL NUMBER OF BARS ON EACH FACE)
TIE BAR NUMBER 4 SPACING 8.00 IN

COLUMN INTERACTION: MOMENT ABOUT Z -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	Staad Input Data.txt
580.16	464.13	207.36	84.77	e-bal.(inch)
M0	P-tens.	Des.Pn	Des.Mn	4.91
39.08	-96.00	8.72	1.40	e/h
				0.08035

COLUMN INTERACTION: MOMENT ABOUT Y -AXIS (KIP-FT)

P0	Pn max	P-bal.	M-bal.	e-bal.(inch)
580.16	464.13	207.36	84.77	4.91
M0	P-tens.	Des.Pn	Des.Mn	e/h
39.08	-96.00	8.72	2.57	0.14720

		Pn	Mn	Pn	Mn	(@ Z)
P0	*	428.43	54.43	214.21	84.42	
	*	392.72	62.91	178.51	82.09	
	*	357.02	69.84	142.81	77.19	
Pn,max	*	321.32	75.23	107.11	71.14	
	*	285.62	79.28	71.40	62.97	
Pn	*	249.92	82.26	35.70	51.70	
NOMINAL	*	Pn	Mn	Pn	Mn	(@ Y)
AXIAL	*	428.43	54.43	214.21	84.42	
COMPRESSION	*	392.72	62.91	178.51	82.09	
Pb	-----*Mb	357.02	69.84	142.81	77.19	
	*	321.32	75.23	107.11	71.14	
	*	285.62	79.28	71.40	62.97	
	* M0 Mn,	249.92	82.26	35.70	51.70	
	* BENDING					
P-tens	* MOMENT					

*****END OF COLUMN DESIGN RESULTS*****

▲ STAAD SPACE

-- PAGE NO. 309

622. END CONCRETE DESIGN

623. FINISH

***** END OF THE STAAD.Pro RUN *****

**** DATE= FEB 12,2018 TIME= 15: 9:35 ****

* For technical assistance on STAAD.Pro, please visit *

* <http://selectservices.bentley.com/en-US/> *

* *

* Details about additional assistance from *

* Bentley and Partners can be found at program menu *

* Help->Technical Support *

* *

* Copyright (c) 1997-2015 Bentley Systems, Inc. *

* <http://www.bentley.com> *

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Appendix B - Staad Technical Reference 5.31.2.16 IBC 2012 Seismic Load Definition

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

5.31.2.16 IBC 2012 Seismic Load Definition

The specifications of the seismic loading chapters of the International Code Council's IBC 2012 code and the ASCE 7-10 code for seismic analysis of a building using a static equivalent approach have been implemented as described in this section. Depending on the definition, equivalent lateral loads will be generated in the horizontal direction(s).



This feature requires STAAD.Pro 2007 (Build 11) or higher. Refer to AD.2007-11.3.7 of the What's New section for additional information on using this feature.

The seismic load generator can be used to generate lateral loads in the X & Z directions for Y up or X & Y for Z up. Y up or Z up is the vertical axis and the direction of gravity loads (See the SET Z UP command in Section 5.5). All vertical coordinates of the floors above the base must be positive and the vertical axis must be perpendicular to the floors.

The rules described in section 1613 of the ICC IBC-2012 code (except 1613.5.5) have been implemented. This section directs the engineer to the ASCE 7-2010 code. The specific section numbers of ASCE 7—those which are implemented, and those which are not implemented—are shown in the table below.

Table 5-22: Sections of IBC 2012 implemented and omitted in the program

Implemented sections of IBC 2012 (ASCE 7-10)	Omitted sections of IBC 2012 (ASCE 7-10)
11.4	12.8.4.1
11.5	12.8.4.3 and onwards
12.8	

Steps used to calculate and distribute the base shear are as follows:

1. The Time Period of the structure is calculated based on section 12.8.2.1 of ASCE 7-10 (IBC 2012). This is reported in the output as Ta.
2. The period is also calculated in accordance with the Rayleigh method. This is reported in the output as T.
3. You may override the Rayleigh based period by specifying a value for PX or PZ (Items f7 and f8) depending on the direction of the IBC load.
4. The governing Time Period of the structure is then chosen between the above two periods, and the additional guidance provided in section 12.8.2 of ASCE 7-10 (IBC 2012). The resulting value is reported as "Time Period used" in the output file.
5. The Design Base Shear is calculated based on equation 12.8-1 of ASCE 7-10 (IBC 2012). It is then distributed at each floor using the rules of clause 12.8.3, equations 12.8-11, 12.8-12 and 12.8-13 of ASCE 7-10.
6. If the ACCIDENTAL option is specified, the program calculates the additional torsional moment. The lever arm for calculating the torsional moment is obtained as 5% of the building dimension at each floor level perpendicular to the direction of the IBC load (section 12.8.4.2 of ASCE 7-10 for IBC 2012). At each joint where a weight is located, the lateral seismic force acting at that joint is multiplied by this lever arm to obtain the torsional moment at that joint.
7. The amplification of accidental torsional moment, as described in Section 12.8.4.3 of the ASCE 7-10 code, is not implemented.
8. The story drift determination as explained in Section 12.8.6 of the ASCE 7-10 code is not implemented in STAAD.

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Methodology

The design base shear is computed in accordance with the following equation (equation 12.8-1 of ASCE 7-10):

$$V = C_s W$$

The seismic response coefficient, C_s , is determined in accordance with the following equation (equation 12.8-2 of ASCE 7-10):

$$C_s = S_{DS} / [R / I_E]$$

For IBC 2012, C_s need not exceed the following limits defined in ASCE 7-10 (equations 12.8-3 and 12.8-4):

$$C_s = S_{D1} / [T \cdot (R / I)] \text{ for } T \leq T_L$$

$$C_s = S_{D1} \cdot T_L / [T^2 (R / I)] \text{ for } T > T_L$$

However, C_s shall not be less than (equation 12.8-5 of ASCE 7-10):

$$C_s = 0.044 \cdot S_{DS} \cdot I \geq 0.01$$

In addition, per equation 12.8-6 of ASCE 7-10, for structures located where S_1 is equal to or greater than 0.6g, C_s shall not be less than:

$$C_s = 0.5 \cdot S_1 / (R / I)$$

For an explanation of the terms used in the above equations, please refer to the IBC 2012 and ASCE 7-10 codes.

General Format

There are two stages of command specification for generating lateral loads. This is the first stage and is activated through the DEFINE IBC 2012 LOAD command.

DEFINE IBC 2012 (ACCIDENTAL) LOAD

map-spec ibc12-spec

SELFWEIGHT

JOINT WEIGHT

joint-list WEIGHT w

...

See

See "UBC 1994 or 1985 Load Definition" for complete weight input definition.

Where:

map-spec = { ZIP f₁ | LAT f₂ LONG f₃ | SS f₄ S1 f₅ }

ibc12-spec = { RX f₆ RZ f₇ I f₈ TL f₉ SCLASS f₁₀ (CT f₁₁) (PX f₁₂) (PZ f₁₃) (K f₁₄) (FA f₁₅) (FV f₁₆) }

f₁ = The zip code of the site location to determine the latitude and longitude and consequently the Ss and S1 factors. (ASCE 7-10 Chapter 22).

f₂, f₃ = The latitude and longitude, respectively, of the site used with the longitude to determine the Ss and S1 factors. (ASCE 7-10 Chapter 22).

f₄ = The mapped MCE for 0.2s spectral response acceleration. (IBC 2012 Clause 1613.5.1, ASCE 7-10 Clause 11.4.1).

f₅ = The mapped MCE spectral response acceleration at a period of 1 second as determined in accordance with Section 11.4.1 ASCE7-10

f₆ = The response modification factor for lateral load along the X direction, (ASCE Table 12.2.1). This is the value used in "R" in the equations shown above for calculating C_s.

f₇ = The response modification factor for lateral load along the Z direction, (ASCE Table 12.2.1) This is the value used in "R" in the equations shown above for calculating C_s.

f₈ = Occupancy importance factor. (IBC 2012 Clause 1604.5, ASCE 7-10 Table 11.5-1)

f₉ = Long-Period transition period in seconds. (ASCE 7-10 Clause 11.4.5 and Chapter 22).

f₁₀ = Site class. Enter 1 through 6 in place of A through F, see table below. (IBC 2012 clause 1613.3.2, ASCE 7-10 Section 20.3)

The Soil Profile Type parameter SCLASS can take on values from 1 to 6. These relate to the values shown in Site Class Definitions Table in the following manner:

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Table 5-23: Values of IBC soil class (SCLASS) used in STAAD

IBC Class	SCLASS value
A	1
B	2
C	3
D	4
E	5
F	6

f_{11} = Optional CT value to calculate time period. (ASCE 7-10 Table 12.8-2).

f_{12} = Optional Period of structure (in sec) in X-direction to be used as fundamental period of the structure. If not entered the value is calculated from the code. (ASCE 7-10 Table 12.8-2).

f_{13} = Optional Period of structure (in sec) in Z-direction to be used as fundamental period of the structure. If not entered the value is calculated from the code. (ASCE 7-10 Table 12.8-2).

f_{14} = Exponent value, x , used in equation 12.8-7, ASCE 7. (ASCE 7-2005 table 12.8-2 page 129).

f_{15} = Optional Short-Period site coefficient at 0.2s. Value must be provided if SCLASS set to F (i.e., 6). (IBC 2012 Clause 1613.3.3, ASCE 7-10 Section 11.4.3).

f_{16} = Optional Long-Period site coefficient at 1.0s. Value must be provided if SCLASS set to F (i.e., 6). (IBC 2012 Clause 1613.3.3, ASCE 7-10 Section 11.4.3).

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Appendix C - Staad Technical Reference 5.31.3 Definition of Wind load

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

5.31.3 Definition of Wind Load

This set of commands may be used to define some of the parameters for generation of wind loads on the structure. See [Section 5.32.12](#) for the definition of wind direction and the possible surfaces to be loaded. [Section 1.17.3](#) of this manual describes the two types of structures on which this load generation can be performed.

The wind load generator can be used to generate lateral loads in the horizontal—X and Z (or Y if Z up) —directions only.

- ✓ The graphical user interface can be used to automatically generate the appropriate intensity values via the [ASCE-7: Wind Load dialog](#). See ["Persistence of Parameters used to Generate ASCE Wind Loads"](#)

General Format

DEFINE WIND LOAD

TYPE *j* (*optional_comment*)

{ *intensity-definition* | *code-parameters* }

EXPOSURE *e*₁ { **JOINT** *joint-list* | **YRANGE** *f*₁ *f*₂ | **ZRANGE** *f*₁ *f*₂ }

Repeat **EXPOSURE** command up to 98 times.

Where:

intensity-definition or *code-parameters* data is entered based on either custom or Russian code wind definitions. See ["Wind Intensity Definition"](#) or See ["Russian Wind Loads"](#)

j = wind load system type number (integer)

optional_comment = A text string comment or description used to help identify the wind load type.

*p*₁, *p*₂, *p*₃... *p*_{*n*} = wind intensities (pressures) in force/area. Up to 100 different intensities can be defined in the input file per type.

*h*₁, *h*₂, *h*₃... *h*_{*n*} = corresponding heights in global vertical direction, measured in terms of actual Y (or Z for Z UP) coordinates up to which the corresponding intensities occur.

*c*₁, *c*₂ ... *c*_{*m*} = exposure factors. A value of 1.0 means that the wind force may be applied on the full influence area associated with the joint(s) if they are also exposed to the wind load direction. Limit: 99 factors.

joint-list = Joint list associated with Exposure Factor (joint numbers or TO or BY) or enter only a group name.

*f*₁ and *f*₂ = global coordinate values to specify Y (or Z if Z UP) vertical range for Exposure Factor. Use **YRANGE** when Y is Up and **ZRANGE** when Z is Up (See the **SET Z UP** command in [Section 5.5](#)).

If the command **EXPOSURE** is not specified or if a joint is not listed in an Exposure, the exposure factor for those joints is chosen as 1.0.

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Wind Intensity Definition

For custom (including for ASCE 7) wind load definitions, the wind intensity at heights above ground are defined as follows:

intensity-definition = INTENSITY p₁ p₂ p₃ ... p_n HEIGHT h₁ h₂ h₃ ... h_n

 **These values are automatically generated for ASCE 7 wind loads when the ASCE-7: Wind Load dialog is used.**

All intensities and heights are in current unit system. The heights specified are in terms of actual Y coordinate (or Z coordinates for Z UP) and not measured relative to the base of the structure. The first value of intensity (p₁) will be applied to any part of the structure for which the Y coordinate (or Z coordinate for Z UP) is equal to or less than h₁. The second intensity (p₂) will be applied to any part of the structure that has vertical coordinates between the first two heights (h₁ and h₂) and so on. Any part of the structure that has vertical coordinates greater than h_n will be loaded with intensity p_n.

Only exposed surfaces bounded by members (not by plates or solids) will be used. The joint influence areas are computed based on surface member selection data entered in [section 5.32.12](#) and based on the wind direction for a load case. Only joints actually exposed to the wind and connected to members will be loaded. The individual bounded areas must be planar surfaces, to a close tolerance, or they will not be loaded.

Exposure factor (e) is the fraction of the influence area associated with the joint(s) on which the load may act if it is also exposed to the wind load. Total load on a particular joint is calculated as follows.

Joint load = (Exposure Factor) × (Influence Area) × (Wind Intensity)

The exposure factor may be specified by a joint-list or by giving a vertical range within which all joints will have the same exposure. If an exposure factor is not entered or not specified for a joint, then it defaults to 1.0 for those joints; in which case the entire influence area associated with the joint(s) will be considered.

For load generation on a closed type structure defined as a PLANE FRAME, influence area for each joint is calculated considering unit width perpendicular to the plane of the structure. You can accommodate the actual width by incorporating it in the Exposure Factor as follows.

Exposure Factor (User Specified) = (Fraction of influence area) × (influence width for joint)

Notes

- All intensities, heights and ranges must be provided in the current unit system.
- If necessary, the **INTENSITY** and **EXPOSURE** command lines can be continued on to additional lines by ending all but last line with a space and hyphen (-). Use up to 11 lines for a command.

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Appendix D - Staad Technical Reference 2.4.1.1 Allowable per AISC code

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

2.4.1.1 Allowables per AISC Code

For steel design, STAAD compares the actual stresses with the allowable stresses as defined by the American Institute of Steel Construction (AISC) Code. The ninth edition of the AISC Code, as published in 1989, is used as the basis of this design (except for tension stress). Because of the size and complexity of the AISC codes, it would not be practical to describe every aspect of the steel design in this manual. Instead, a brief description of some of the major allowable stresses are described herein.

2.4.1.1.1 Tension Stress

2.4.1.1.2 Shear Stress

2.4.1.1.3 Stress Due To Compression

2.4.1.1.4 Bending Stress

2.4.1.1.5 Combined Compression and Bending

2.4.1.1.1 Tension Stress

Allowable tensile stress on the net section is calculated as;

$$F_t = 0.60 F_y$$

2.4.1.1.2 Shear Stress

Allowable shear stress on the gross section,

$$F_v = 0.4 F_y$$

2.4.1.1.3 Stress Due To Compression

Allowable compressive stress on the gross section of axially loaded compression members is calculated based on the formula E-1 in the AISC Code, when the largest effective slenderness ratio (Kl/r) is less than C_c . If Kl/r exceeds C_c , allowable compressive stress is decreased as per formula 1E2-2 of the Code.

$$C_c = \sqrt{\frac{2\pi^2 E}{F_y}}$$

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

2.4.1.1.4 Bending Stress

Allowable bending stress for tension and compression for a symmetrical member loaded in the plane of its minor axis, as given in Section 1.5.1.4 is:

$$F_b = 0.66F_y$$

If meeting the requirements of this section of:

- $b_f/2t_f \leq 65/\sqrt{F_y}$
- $b_f/t_f \leq 190/\sqrt{F_y}$
- $d/t \leq 640(1 - 3.74 (f_s/F_y))/\sqrt{F_y}$ when $(f_s/F_y) < 0.16$, or than $257/\sqrt{F_y}$ if $(f_s/F_y) > 0.16$
- The laterally unsupported length shall not exceed $76.0 b_f/F_y$ (except for pipes or tubes), nor $20,000/(d F_y/A_f)$
- The diameter:thickness ratio of pipes shall not exceed $3,300/\sqrt{F_y}$

If for these symmetrical members, $b_f/2t_f$ exceeds $65/\sqrt{F_y}$, but is less than $95/\sqrt{F_y}$, $F_b = F_y(0.79 - 0.002(b_f/2t_f)\sqrt{F_y})$

For other symmetrical members which do not meet the above, F_b is calculated as the larger value computed as per AISC formulas F1-6 or F1-7 and F1-8 as applicable, but not more than $0.60F_y$. An unstiffened member subject to axial compression or compression due to bending is considered fully effective when the width-thickness ratio is not greater than the following:

- $76.0/\sqrt{F_y}$, for single angles or double angles with separators
- $95.0/\sqrt{F_y}$, for double angles in contact
- $127.0/\sqrt{F_y}$, for stems of tees

When the actual width-thickness ratio exceeds these values, the allowable stress is governed by B5 of the AISC code.

Tension and compression for the double symmetric (I & H) sections with $b_f/2t_f$ less than $65/\sqrt{F_y}$ and bent about their minor axis, $F_b = 0.75 F_y$. If $b_f/2t_f$ exceeds $65/\sqrt{F_y}$, but is less than $95/\sqrt{F_y}$, $F_b = F_y(1.075 - 0.005(b_f/2t_f)\sqrt{F_y})$.

For tubes, meeting the subparagraphs b and c of this Section, bent about the minor axis, $F_b = 0.66F_y$; failing the subparagraphs B and C but with a width:thickness ratio less than $238/\sqrt{F_y}$, $F_b = 0.6F_y$.

2.4.1.1.5 Combined Compression and Bending

Members subjected to both axial compression and bending stresses are proportioned to satisfy AISC formula H1-1 and H1-2 when f_a/F_a is greater than 0.15, otherwise formula H1-3 is used. It should be noted that during code checking or member selection, if f_a/F_a exceeds unity, the program does not compute the second and third part of the formula H1-1, because this would result in a misleadingly liberal ratio. The value of the coefficient C_m is taken as 0.85 for sidesway and $0.6 - 0.4 (M_1/M_2)$, but not less than 0.4 for no sidesway.

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

Appendix E - Staad Technical Reference 3.7 Column Design

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

3.7 Column Design

Columns design in STAAD per the ACI code is performed for axial force and uniaxial as well as biaxial moments. All active loadings are checked to compute reinforcement. The loading which produces the largest amount of reinforcement is called the critical load. Column design is done for square, rectangular and circular sections. For rectangular and circular sections, reinforcement is always assumed to be equally distributed on all faces. This means that the total number of bars for these sections will always be a multiple of four (4). If the MMAG parameter is specified, the column moments are multiplied by the MMAG value to arrive at the ultimate moments on the column. Since the ACI code no longer requires any minimum eccentricity conditions to be satisfied, such checks are not made.

Method used

Bresler Load Contour Method

Known Values

P_u , M_{uy} , M_{uz} , B , D , Clear cover, F_c , F_y

Ultimate Strain for concrete : 0.003

Steps involved

1. Assume some reinforcement. Minimum reinforcement (1%) is a good amount to start with.
2. Find an approximate arrangement of bars for the assumed reinforcement.
3. Calculate $PN_{MAX} = 0.85 P_o$, where P_o is the maximum axial load capacity of the section. Ensure that the actual nominal load on the column does not exceed PN_{MAX} . If PN_{MAX} is less than P_u/ϕ , (ϕ is the strength reduction factor) increase the reinforcement and repeat steps 2 and 3. If the reinforcement exceeds 8%, the column cannot be designed with its current dimensions.
4. For the assumed reinforcement, bar arrangement and axial load, find the uniaxial moment capacities of the column for the Y and the Z axes, independently. These values are referred to as MY_{CAP} and MZ_{CAP} respectively.

5. Solve the interaction equation:

$$\left(\frac{M_{uy}}{M_{yCAP}}\right)^a + \left(\frac{M_{uz}}{M_{zCAP}}\right)^a \leq 1.0$$

Where $a = 1.24$

If the column is subjected to a uniaxial moment, a is chosen as 1.0

6. If the Interaction equation is satisfied, find an arrangement with available bar sizes, find the uniaxial capacities and solve the interaction equation again. If the equation is satisfied now, the reinforcement details are written to the output file.
7. If the interaction equation is not satisfied, the assumed reinforcement is increased (ensuring that it is under 8%) and steps 2 to 6 are repeated.
8. The maximum spacing of reinforcement closest to the tension force, for purposes of crack control, is given by

$$s = 15 \left(40,000 - \frac{40,000}{f_s} \right) - 2.5cc \leq 12 \left(\frac{40,000}{f_s} \right)$$

	Project:	Proposed Container House	Designed:	-
	Location:	California	Checked:	-
	Client:	-	Approved:	-
	Title:	Structural Calculation	Rev.:	0

with f_s in psi and is permitted to be taken equal to $(2/3) f_y$, rather than 60 percent of f_y , as in ACI 318-02.

9. Section 10.9.3 has been modified to permit the use of spiral reinforcement with specified yield strength of up to 100,000 psi. For spirals with f_{yt} greater than 60,000 psi, only mechanical or welded splices may be used.

Column Interaction

The column interaction values may be obtained by using the design parameter TRACK 1.0 or TRACK 2.0 for the column member. If a value of 2.0 is used for the TRACK parameter, 12 different Pn-Mn pairs, each representing a different point on the Pn-Mn curve are printed. Each of these points represents one of the several Pn-Mn combinations that this column is capable of carrying about the given axis, for the actual reinforcement that the column has been designed for. In the case of circular columns, the values are for any of the radial axes. The values printed for the TRACK 1.0 output are:

P0 = Maximum purely axial load carrying capacity of the column (zero moment).

Pnmax = Maximum allowable axial load on the column (Section 10.3.5 of ACI 318).

P-bal = Axial load capacity at balanced strain condition.

M-bal = Uniaxial moment capacity at balanced strain condition.

e-bal = M-bal / P-bal = Eccentricity at balanced strain condition.

M0 = Moment capacity at zero axial load.

P-tens = Maximum permissible tensile load on the column.

Des. Pn = Pu/PHI where PHI is the Strength Reduction Factor and Pu is the axial load for the critical load case.

Des. Mn = Mu*MMAG/PHI where PHI is the Strength Reduction Factor and Mu is the bending moment for the appropriate axis for the critical load case. For circular columns,

$$M_u = \sqrt{M_{uy}^2 + M_{uz}^2}$$

$$e/h = (M_n/P_n)/h$$

Where:

h is the length of the column.